

Led Cylinder Surface Light Premium

GLI-LCSLP

INSTALL AND MAINTENANCE MANUAL

WARNING

1. Read all instructions.
2. Install in accordance with national and local electrical code regulations.
3. This product is intended to be installed and serviced by a qualified, licensed electrician.
4. Turn off electrical power before installing or servicing luminaire in any way.
5. To reduce the risk of fire and overheating, make sure all connections are tight.



**May result in serious injury or death.
Turn power OFF at circuit breaker
prior to installation or servicing.**

WARNINGS AND CAUTIONS

- **Electrical Safety:** Disconnect power at the circuit breaker before installation or maintenance to avoid electric shock.
- **Qualified Personnel:** Installation must be performed by a licensed electrician in compliance with local codes.
- **Voltage Verification:** Ensure the supply voltage matches the fixture's specifications to prevent damage.
- **Secure Mounting:** Verify that the mounting surface or structure can support the weight of the fixture.
- **Wiring Precautions:** Ensure all wiring connections are properly insulated and secure to prevent hazards.
- **Heat Dissipation:** Ensure adequate clearance around the fixture to allow for proper heat dissipation and prevent overheating.
- **Installation Requirement:** Fixture is NOT SUITABLE for wet locations. Install only in dry or damp environments.

CONTENTS

1. Surface Installation

GLI-LCSLP Led Cylinder Surface Light Premium Installation Instructions

1 SURFACE INSTALLATION

- 1-1. Pull (2) Power and Dimming Feeds through (3) Mounting Plate for recessed or (7) 6" Canopy for surface.
- 1-2. Place (3) Mounting Plate or (7) 6" Canopy on (1) Junction Box and secure with existing box screws or (4) Screw KM4*22.
- 1-3. For surface installation, place (3) Mounting Plate on (7) 6" Canopy and secure with (4) Screw KM4*22.
- 1-4. Connect the fixture wires as follows
 - **Black:** Live/Hot
 - **White:** Neutral
 - **Green:** Ground
 - **Violet:** Dim+ (if applicable)
 - **Pink:** Dim- (if applicable)
- 1-5. If not using dimming, individually cap the dimming wires with wire nuts or approved connectors.
- 1-6. Align (6) Fixture tabs with (3) Mounting Plate Grooves, push in, and twist to lock.

