

Vanity Light A

GLI-VLGA

INSTALL AND MAINTENANCE MANUAL

WARNING

1. Read all instructions.
2. Install in accordance with national and local electrical code regulations.
3. This product is intended to be installed and serviced by a qualified, licensed electrician.
4. Turn off electrical power before installing or servicing luminaire in any way.
5. To reduce the risk of fire and overheating, make sure all connections are tight.



**May result in serious injury or death.
Turn power OFF at circuit breaker
prior to installation or servicing.**

Vanity Light A

CAUTION

- Before connecting the light, verify that the input voltage is compatible to prevent damage.
- Carefully check for any signs of damage upon opening the package.
- Before connecting to the power supply, switch off the breaker and verify that it is off to prevent electric shock.
- To prevent damage, avoid exposing wiring to sharp edges or objects.

INSTALLATION INSTRUCTIONS

PRE-INSTALLATION

Before beginning installation, turn OFF power from the electrical panel.

STEP 1

Attach the mounting plate to the outlet box by using two mounting screws.

STEP 2

Pull out the wires and grounding wire from the outlet box.

Make wire connections using the wire nuts, as follow:

- Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source.
- Connect the neutral wire (usually white insulation) from the fixture to the white wire from the power source.
- Attach the fixture grounding wire (usually green insulation or bare wire) to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with the wire nut.

Carefully put the wires back into the outlet box.

Vanity Light A

INSTALLATION INSTRUCTIONS

STEP 3

Attach the back plate to the mounting plate by inserting the screws.

