

Vapor Tight IH

Project: _____ Location: _____ Type: _____

Model Number: _____ Qty: _____ Notes: _____ Date: _____



GLI-VTIH

Vapor Tight IH

GOled Vapor Tight IH is a robust lighting solution suitable for both indoor and outdoor environments, including hallways, parkades, stairwells, and service areas. You can significantly reduce installation costs with the optional linkable power feed, making it a cost-effective choice.

Features and Specifications

- Heavy duty shell is light and corrosion resistant
- Aluminum heatsink body provides efficient cooling for long life operation
- Impact resistant acrylic lens
- Surface or pendant installation
- Quick connect power cable eliminates time consuming costs
- Lights can be linked with jumper cables, further reducing costs
 - * Maximum 4pcs 4ft lights per power feed
 - * Maximum 3pcs 8ft lights per power feed
- Industry leading driver efficiency of 130LM/W
- 0-10V dimming
- Wide range of operational temperature, -15°C to +40°C

Certifications

- cULus Listed
- Wet location rated
- IP65 rated
- DLC premium listed

Warranty


- 5 years warranty
- Estimated lifespan of over 50 000 hours

Overview


Light source	LED
Watts (W)	32W, 64W
Voltage	120V-270V
Lumen output (LM)	4160LM, 8320LM
Efficiency (LM/W)	130LM/W
Color temperature (K)	3000K, 4000K, 5000K
CRI	80CRI

DIMENSIONS


8ft front view




8ft side view



4ft front view



4ft side view



SPECIFICATIONS

CODE	WATTAGE	LUMENS	LUMENS/WATT	CCT	CRI	RATED LIFETIME
GLI-VTIH-4	32W	4160LM	130LM/W	30K/40K/50K	80CRI	50 000 hours
GLI-VTIH-8	64W	8320LM	130LM/W	30K/40K/50K	80CRI	50 000 hours

ORDERING GUIDE

SERIES	SIZE/WATTAGE	CCT	CONTROL	MOUNTING	CONNECTOR
GLI-VTIH					
	4 - 4ft 32 Watts	30K - 3000K	NC - No control	CS - Cable suspension	PC - Power cable
	8 - 8ft 64 Watts	40K - 4000K	DM - 0-10V	SM - Surface	LN - Linking jumper cable
		50K - 5000K			